

## NETWORK MANAGEMENT SYSTEM

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223  
2224  
2225  
2226  
2227  
2228

## BACKGROUND OF THE INVENTION

The present invention relates in general to a network management system. More particularly, the invention relates to a network management system for managing a network system to which a plurality of networks the address systems of which are different from one another are connected.

IP addresses as network addresses which are currently most widely utilized in the Internet and the like are prescribed in accordance with the protocol called the IPv4 (Internet Protocol ver. 4) and also are addresses each having the address space of 32 bits. The network addresses must be uniquely allocated to apparatuses connected to the network, respectively, and hence the allocation of the network addresses to the apparatuses connected to the Internet has been carried out by the organ called NIC or the like in such a way as to become unique. Since in the IPv4, each of the IP addresses has the address space of 32 bits, the addresses of 2 to the 32-th power, i.e., four billions at maximum can be theoretically allocated. However, as the number of apparatuses connected to the Internet is increased, it becomes difficult to allocate the IP addresses of the IPv4 to all of the apparatuses connected to the Internet.

The technique which is widely used as the technique for solving the above-mentioned problem is the method wherein the address translation function described in RFC1631 (The IP Network Address Translator) decided by the IETF is combined with the private network described in RFC1918 (Address Allocation for Private Internets). The method is established on the assumption that for example, all of the apparatuses which are present in the local network such as the network within industry are not necessarily connected to the external network such as the Internet. In other words, first of all, the local network such as network within industry allocates the IP address using the address which falls within the private address described in RFC1918 to construct the network. At this time, with this private address, the associated apparatuses are not connected to the external network such as the Internet. With respect to the apparatuses connected to the external network such as the Internet, the address translator described in RFC1613 is disposed between the local network and the external network such as the Internet, and the address of the transmission/reception packet is translated through the address translation from the private address into the global address with which the access is given to the Internet, thereby making the connection to the Internet possible. Now, by the global address is meant the address which is allocated by the NIC or the like. At this time,

there is also made the device in which the infinite global addresses are effectively utilized in such a way that the global addresses are dynamically allocated to make it possible that a plurality of local nodes hold one global address in common on the basis of the time-sharing.

Now, in the address translation described in RFC1631, the rewriting of the transmission source IP address and the transmission destination IP address which are contained in the header of the IP packet, and the change of the check sum of the IP header which is generated along with the rewriting are recalculated to replace them with each other. As a result, the communication by TCP/IP becomes possible, and the communication according to the protocol of the upper layer with respect thereto also becomes possible.

However, though in the network management protocol such as the SNMP, the IP address is contained in a protocol data unit (PDU) as well in which the data is exchanged in accordance with the management protocol, this part is not subjected to the address translation in the address translator described in RFC1631.

On the other hand, in JP-A-11-187058, in addition to the function of the address translation described in RFC1631, the address translator having the function of carrying out the address translation with respect to the protocol data unit as well of the

management protocol is described.

#### SUMMARY OF THE INVENTION

However, if the operation based on the private address and the global address is carried out  
5 by the address translator, then this operation will be carried out through the communication in accordance with the management protocol using the global address which can be used in the network on the side of the manager node. For this reason, the communication in  
10 accordance with the management protocol can be carried out only with the node which is located on the managed side and to which the global address is already allocated. However, if in the network management, the management can be carried out for the node as well  
15 which has not such a global address allocated thereto, it becomes possible to carry out the more effective management. This respect is not disclosed in the method described in JP-A-11-187058.

In the light of the foregoing, the present  
20 invention has been made in order to solve the above-mentioned problems associated with the prior art, and it is therefore an object of the present invention to provide a network management system in which the data communication in accordance with a management protocol  
25 can be carried out even between nodes each not having a global address in a network system in which networks of different address systems are connected to one another

through an address translator.

As one means for attaining the above-mentioned object, according to the present invention, there is provided a network management system for  
5 managing a network system in which a first network and a second network which are different in address system from each other are connected to each other through an address translator, wherein each of the first and second networks includes a node and a management  
10 protocol proxy, and each of the management protocol proxies includes a management protocol proxy data generating unit for treating, as the management protocol proxy data, a transmission source address, a transmission destination address and data in a protocol  
15 data unit which are contained in a packet of a management protocol sent from a node, and an address translation unit for translating address information within a protocol data unit contained in management protocol proxy data sent from another management protocol proxy.

20 As a result, it is possible to carry out the data communication between the proxies of the management protocol, and it is also possible to carry out the data communication between the nodes each not having the global address.

## 25 BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects as well as advantages of the present invention will become clear

by the following description of the preferred embodiments of the present invention with reference to the accompanying drawings, wherein:

Fig. 1 is a diagram showing a basic configuration of a network system;

Fig. 2 is a diagram showing a structure of a packet of an SNMP message;

Fig. 3 is a diagram showing a structure of a packet of management protocol proxy data;

Fig. 4 is a diagram useful in explaining a function of an NAT;

Fig. 5 is a diagram showing a structure of a packet of an SNMP message;

Fig. 6 is a diagram showing a structure of a packet of an SNMP message;

Fig. 7 is a diagram showing one application example in a virtual network management system;

Fig. 8 is a diagram showing one application example in a virtual network management system;

Fig. 9 is a diagram showing one application example in a virtual network management system;

Fig. 10 is a diagram showing one application example in a virtual network management system;

Fig. 11 is a diagram showing one application example in a virtual network management system;

Fig. 12 is a block diagram showing a configuration of a management protocol proxy on the managed side;

Fig. 13 is a block diagram showing a configuration of a management protocol proxy on the managing side;

Fig. 14 is a diagram showing one example of  
5 management protocol proxy data;

Fig. 15 is a block diagram showing a configuration of a proxy data disassembly/assembly unit;

Fig. 16 is a diagram showing a definition example of the other party proxy definition;

10 Fig. 17 is a flow chart useful in explaining the processing of assembling proxy data;

Fig. 18 is a flow chart useful in explaining the processing of disassembling proxy data;

Fig. 19 is a block diagram showing a configuration of an address translation processing unit;  
15

Fig. 20 is a block diagram showing a configuration of an object identifier address translation unit;

Fig. 21 is a flow chart useful in explaining  
20 the processing executed in a PDU analysis/translation unit;

Fig. 22 is a diagram useful in explaining the relationship among a kind of PDU, the direction of transmitting a PDU and the translation direction of the  
25 address translation;

Fig. 23 is a flow chart useful in explaining the processing in a translation subject object identifier extraction unit;



Fig. 24 is a diagram showing a definition example of the address translation definition;

Fig. 25 is a diagram showing an example of a configuration of a virtual network management system;

5 Fig. 26 is a block diagram showing a configuration of a management protocol proxy;

Fig. 27 is a block diagram showing a configuration of a management protocol proxy;

Fig. 28 is a diagram showing an example of a  
10 configuration of a virtual network management system;  
and

Fig. 29 is a block diagram showing a configuration of a management protocol proxy on the managed side.

15 DESCRIPTION OF THE EMBODIMENTS

The preferred embodiments when an SNMP is applied to a management protocol will hereinafter be described in detail with reference to the accompanying drawings.

20 Fig. 1 is a diagram showing the concept of a network management system which will be described in the present embodiment.

The present system includes a global network 10, a private network A 30a and a private network B  
25 30b. Then, the private network A 30a is connected to the global network 10 through an NAT 20a for carrying out the address translation, while the private network

B 30b is connected to the global network 10 through an NAT 20b for carrying out the address translation.

A node 80 for carrying out the monitoring is connected to the private network A 30a. This node 80  
5 includes a manager 40 for executing the processing for monitoring managed nodes, and a management protocol proxy 60a for carrying out the generation of proxy data of the management protocol, the address translation within a protocol data unit contained in the proxy  
10 data, and the like.

In addition, nodes 50 and 90 as the managed nodes, and the management protocol proxy server 60b for carrying out the generation of proxy data of the management protocol, the address translation within a  
15 protocol data unit contained in the proxy data, and the like are connected to the private network B 30b.

In such a configuration, in the present network management system, the node 80 for carrying out the monitoring is adapted to manage the nodes 50 and 90  
20 as the managed nodes.

When the data communication is intended to be carried out with the node 50 as the managed node through the manager 40 of the node 80 of the private network 30a, the data communication is carried out  
25 between the management protocol proxy 60a of the node 80 and the management protocol proxy server 60b of the private network B 30b. This becomes equivalent to that a virtual communication path called an interproxy

communication path 70 is formed.

If such a configuration is adopted, then the data communication can be carried out between the networks when the address used in the private network A 30a is different from that used in the private network B 30b, i.e., when their address systems are different from each other. In addition, even in the case where a fire wall or the like which is adopted to block the passage of any of the addresses of the private networks and the address of the global network is formed between the private network A 30a and the private network B 30b, the data communication can be made possible.

The operation of the overall network system shown in Fig. 1 will hereinbelow be described more concretely.

Fig. 2 is a diagram showing an SNMP message packet of a management protocol SNMP of the node. Fig. 3 is a diagram showing a packet of management protocol proxy data of the management protocol proxy server. That is, the management protocol proxy 60a and the management protocol proxy server 60b store the transmission source information and the transmission destination information which have been respectively held as the transmission destination and the transmission source within the header of an IP layer as a network layer in the management protocol proxy data corresponding to the data of an application layer from the packets of the management protocol SNMPS which have

been respectively sent from the manager 40 of the node 80, and the node 50 and the node 90 as the managed nodes. Further, as for a transport layer of the packet of the management protocol proxy data, for example, a TCP of a connection type is employed. In addition, the transmission destination and the transmission source of the management protocol proxy data itself become the management protocol proxy or the management protocol proxy server.

Now, the description will hereinbelow be given with respect to the flow of the data when the communication is carried out from the manager 40 to the node 50 or the node 90 as the managed node and in the direction opposite thereto, i.e., from the node 50 or the node 90 as the managed node to the manager 40 through the management protocol proxy 60a and the management protocol proxy server 60b. At the time when the data of the management protocol sent by the node 40 as the manager has been delivered to the management protocol proxy 60a, the management protocol proxy 60a combines the data itself of the management protocol with the information exhibiting the essential transmission destination and transmission source of the data of the management protocol to generate the management protocol proxy data and sends the management protocol proxy data thus generated to the management protocol proxy server 60b. Then, the management protocol proxy server 60b fetches the data of the management protocol

and the information exhibiting the essential transmission destination from the received management protocol proxy data to reconstruct the packet of the management protocol to send the packet thus

- 5 reconstructed to the node 50 as the managed node which is the essential transmission destination. At this time, the transmission source of the packet of the management protocol is made the management protocol proxy server 60b, whereby the response from the node 50
- 10 is sent to the management protocol proxy server 60b. Then, the management protocol proxy server 60b which has received the response packet of the management protocol from the node 50 translates that response packet into the management proxy protocol data to
- 15 return the resultant management proxy protocol data back to the management protocol proxy 60a. Then, the management protocol proxy 60a reconstructs the response packet of the management protocol from the management protocol proxy data to return the resultant response
- 20 packet back to the manager 40.

In such a manner as described above, in the environment in which the communication can not be directly carried out between the nodes using the management protocol, the communication in accordance

25 with the management protocol can be carried out through the management protocol proxy and the management protocol proxy server.

Further, each of the management protocol

proxy and the management protocol proxy server includes an address translation function of translating the address of the PDU part of the management protocol. As a result, the address of the node contained in the  
5 protocol data unit (hereinafter, referred to as "the PDU" for short, when applicable) of the management protocol of the node is translated into the virtual address which is used to manage the network, whereby the management can be carried out as if the node has  
10 the virtual address. The virtual address which is used only in the network management at this time is referred to as "the management address" for short when applicable in the present embodiment for the sake of convenience.

15 By the way, while in the configuration shown in Fig. 1, the description has been given with respect to the case where the management protocol proxy 60a is realized in the form of the program, similarly, the function of the management protocol proxy server 60b  
20 can also be realized in the form of the program. In this case, the program is recorded in a magnetic disk, an optical disc or a magneto-optical disc from which the data can be read out by a computer, and the node which takes charge of the function of the management  
25 protocol proxy server is adapted to read out the program to execute the program.

Next, the NAT shown in Fig. 1 will hereinbelow be described. Each of the NATs shown in Fig. 1

is in conformity to RFC1631.

Fig. 4 is a diagram useful in explaining the function of the NAT. As shown in the figure, the description will hereinbelow be given with respect to the case where in the network in which a global network 10 and a private network 30 are connected to each other through an NAT 20, an address G0 is allocated as a global address 200 to a node 40, an address L1 is allocated as a private address 210 to the managed node, and an address G1 is allocated as the global address 200 to the managed node. In this case, a translation table 230 in which the global address and the private address are made correspond to each other is provided in the NAT 20. As a result, the packet, with respect to the address G1, is transmitted from the node 40 side to the node 50 side. The NAT 20 translates the transmission destination address of the packet directed to the address G1 from the global address G1 to the private address L1 in accordance with the translation table 230 to transmit the resultant address to the private network side. That is, when having reached the NAT 20 from the node 40 side as shown in Fig. 5, the packet of interest is the packet in which the information of the address G1 for the transmission destination is contained as the header information of the IP layer part corresponding to the network layer, while when being relayed from the NAT 20 towards the node on the private network side, is transmitted as the packet in

which the information of the address L1 is contained as the header information of the IP layer part as shown in Fig. 6 in the transmission destination. On the other hand, in the case where the packet is transmitted from the node 50 on the private network side towards the node 40 on the global network side, when having reached the NAT 20 from the node 50, the packet of interest is the packet in which the information of L1 for the transmission source is contained as the header information of the IP layer part, while when being relayed from the NAT 20 towards the node 40 on the global network side, is transmitted as the packet in which the information of G1 for the transmission source is contained as the header information of the IP layer part.

On the basis of such a function of the NAT 20, as for the setting of the network of the node 50 itself, the setting has only to be made in such a way that the network of the node 50 itself has the private address L1. Then, when the node 50 is intended to communicate with another apparatus within the private network, the communication can be carried out using the private address L1. In addition, when the communication is intended to be carried out with the apparatus on the global network side, the communication can be carried out using the global address G1 allocated by the NAT 20.

By the way, in this case, the NAT has been



described as the translator having the function of carrying out the address translation of the IP layer (the address translation of the PDU part of the management protocol can not be carried out). In the network utilizing such an NAT, as has already been described, the address of the PDU part of the management protocol is translated in the management protocol proxy server.

The more concrete network system will herein-  
below be described.

Fig. 7 is one of application examples in the network management system and shows a configuration in the case where the management is carried out by using the proper global address allocated to a managed side node as the address which is used to manage the network.

A managed node a 50a has the address L1 as the private address 210. This address of L1 is the private address, and hence is the address which can be used only in the private network B 30b.

Furthermore, as for address translation 230 in the NAT 20b, the global address G1 is made correspond to the private address L1, and the address G1 is statically allocated as the global address to the managed node a 50a. When the global network 10 or the private network A 30a is intended to communicate directly with the managed node a 50a, the communication is carried out using the global address G1.

Now, as for address translation 220 in the management protocol proxy 60b, the management address G1 is made correspond to the private address L1, whereby with respect to the management protocol data which is to be sent from the managing side to the managed side, the global address G1 is translated into the private address L1, while with respect to the management protocol data which is to be sent from the managed side to the managing side, the private address L1 is translated into the global address G1.

As a result, if reference is made to the data of the management protocol using the management protocol from the manager side, the managed node a 50a seems to be as if it has the global address G1.

For this reason, as for the management information 240 in the manager 40, the managed node a 50a is made correspond to the apparatus having the address G1, and hence the network management can be carried out using the address G1.

Next, Fig. 8 shows the case where the global address to be allocated to the managed node by the NAT 20b is dynamically allocated thereto.

In general, the number of global addresses which can be used for the external connection in the private networks which are connected through the NATs is less than the number of apparatuses within the private networks. As for the method of utilizing effectively the less global addresses, there is

employed the method wherein the allocation of the global address to the apparatus is carried out only for a period of time when the apparatus of interest is connected to the outside, and at the time when the connection of the apparatus of interest to the outside has been completed, the global address which the apparatus of interest has used is adapted to be reutilized by another apparatus. In the case where the global addresses are dynamically allocated in such a manner, in general, the global address which is allocated to a certain one apparatus differs as the case may be.

In such a case, as the address translation 230 in the NAT 20b, the global address Gx is made correspond to the private address L1. Then, the global address Gx is the address which is selected among the addresses of the fixed choices as the case may be, and hence the address Gx is dynamically allocated as the global address to the managed node a 50a at least at that time. What address is allocated is determined by the NAT 20b.

Now, if the address Gx is used as the management address as it is, then the address which is made correspond as the management information 240 in the manager 40 to the managed node a 50a changes as the case may be, and hence the continuation of the management can not be maintained so that the proper network management can not be carried out. This is a problem.

Then, as for the address translation 220 in the management protocol proxy 60b, as shown in Fig. 8, the virtual address of V1 which is completely different from the address Gx is statically allocated. As a result, as for the management information 240 in the manager, the managed node a 50a is made correspond to the apparatus having the address V1 and hence the network management can be properly carried out.

Fig. 9 shows an example in the case where there are a plurality of private networks on the managed side, and the private addresses of the managed nodes within these private networks compete with one another.

A managed node b 50b is present in the private network B 30b and has the private address L1. On the other hand, a managed node c 50c is present in a private network C 30c and has the private address L1. While the respective addresses conflict with each other, since the private address is used only within the associated one of the private networks in terms of the communication, the networks are not confused at all.

However, if the management protocol data is directly acquired from the managed node b 50b and the managed node C 50c using the management protocol, since both of these apparatuses respond to the information as the apparatus having the private address L1, there arises the problem that the manager is confused so that

the network management can not be properly carried out.

Then, as shown in Fig. 9, with respect to the managed node b 50b, the management address V1 is made correspond to the private address L1 during the address translation 220b in the management protocol proxy 60b, while with respect to the managed node C 50c, the management address V2 is made correspond to the private address L1 during the address translation 220c in the management protocol proxy 60c. That is, the management address V1 and the management address V2 are statically allocated to the managed node b 50b and the managed node c 50c, respectively.

As a result, as for the management information 240 in the manager, the managed node b is decided as the apparatus having the management address V1, and the managed node c is decided as the apparatus having the management address V2 so that the network management can be properly carried out.

Fig. 10 shows an example in the case where the management address is allocated to even the apparatus to which the global address is not allocated, i.e., which is not connected to the outside in order to carry out the network management in the private network.

A managed node a 50a has the address L1 as the private address 210a. In addition, as for the address translation 230 in the NAT 20b, the global address G1 is made correspond to the private address

L1, and the address G1 is statically allocated as the global address to the managed node a 50a. When the global network 10 or the private network A 30a intends to communicate directly with the managed node a 50a, the communication is carried out using the global address G1.

On the other hand, the managed node b 50b has the address L1 as the private address 210b. However, as for the address translation 230 in the NAT 20b, the global address corresponding to the private address L2 is not defined, and hence the global network 10 or the private network A 30a can not communicate directly with the managed node b 50b. But, in this case as well, the manager 40 can exchange the information with the managed node 50 as well in accordance with the management protocol through the management protocol proxy.

At this time, during the address translation 220 in the management protocol proxy 60b, the management address V1 is made correspond to the private address L1, and also the management address V2 is made correspond to the private address 22. That is, the management address V1 is statically allocated to the managed node a 50a, and also the management address V2 is statically allocated to the managed node b 50b. As a result, as for the management information 240 in the manager, the managed node a 50a is decided as the apparatus having the management address V1, and the managed node b 50b is decided as the apparatus having

the management address V2 in order to carry out the network management.

Fig. 11 shows an example in which when the management address is allocated to even the apparatus to which the global address is not allocated, i.e., which is not connected to the outside in the private network in order to carry out the network management, with respect to the apparatus to which the global address is allocated, the global address is used for the management address, while with respect to the apparatus to which the global address is not allocated, the virtual address is used therefor.

The managed node a 50a has the address L1 as the private address 210a. In addition, as for the address translation 230 in the NAT 20b, the global address G1 is made correspond to the private address L1, and the address G1 is statically allocated as the global address to the managed node a 50a. When the global network 10 or the private network A 30a intends to communicate directly with the managed node a 50a, the communication is carried out using the global address G1.

On the other hand, the managed node b 50b has the address L2 as the private address 210b. However, as for the address translation 230 in the NAT 20b, the global address corresponding to the private address L2 is not defined, and hence the global network 10 or the private network A 30a can not communicate directly with

the managed node b 50b. But, in this case as well, the manager 40 can exchange the information with the managed node 50b as well in accordance with the management protocol through the management protocol proxy.

5           At this time, during the address translation 220 in the management protocol proxy 60b, the management address G1 is made correspond to the private address L1, and also the management address V2 is made correspond to the private address L2. That is, the  
10 management address G1 is statically allocated to the managed node a 50a and also the management address V2 is statically allocated to the managed node b 50b. As a result, as for the management information 240 in the manager, the managed node a 50a is decided as the  
15 apparatus having the address G1, and the managed node b 50b is decided as the apparatus having the address V2 in order to carry out the network management.

Subsequently, the configuration of the management protocol proxy will hereinbelow be described  
20 with reference to Fig. 12 and Fig. 13.

Fig. 12 is a block diagram showing a configuration of the management protocol proxy on the managed side.

The management protocol proxy 60b on the  
25 managed side includes: an interproxy communication unit 61 for processing the establishment of the interproxy communication path 70 between the management protocol proxy 60a on the managing side and the unit 61 and the



transmission/reception of the management protocol proxy data; a proxy data assembly/disassembly unit 62 for processing the disassembly/assembly management protocol proxy data; an address translation processing unit 63  
5 for subjecting the address information within the PDU of the management protocol to the address translation; an ASN.1MIB define statement and an address translation definition 65 each of which becomes an input to the address translation processing unit; and an SNMR  
10 message transmission/reception unit 66 for transmitting/receiving the SNMP message between the managed node and the unit 66.

At the time when the message of the management protocol issued from the manager 40 has been  
15 translated into the management protocol proxy data by the management protocol proxy 60a on the managing side to be transmitted to the management protocol proxy on the managed side, first of all, the interproxy communication unit 61 receives the management protocol  
20 proxy data transmitted thereto to deliver the management protocol proxy data thus received to the proxy data assembly/disassembly unit 62. Then, the proxy data assembly/disassembly unit 62 disassembles the received management protocol proxy data to deliver the  
25 management protocol proxy data thus disassembled to the address translation processing unit 63. Then, the address translation processing unit 63 subjects the transmission source address data and the transmission

destination address data of the management protocol proxy data thus delivered thereto and the address information within the PDU of the management protocol into the address translation in accordance with the

5 ASN.1MIB define statement 64 and the address translation definition 65 to deliver the translation result to the proxy data disassembly/assembly unit 62. Then, the proxy data assembly/disassembly unit 62 fetches the transmission destination information, the transmission

10 source information, and the PDU of the management protocol from the proxy data to deliver the information and the PDU thus fetched to the SNMP message transmission/reception unit 66. Then, the SNMP message transmission/reception unit 66 transmits the PDU of the

15 management protocol to the managed node 50 which has been specified as the transmission destination. That is, the SNMP message transmission/reception unit 66 transmits the SNMP message to the managed node 50. Then, the managed node 50 returns the response

20 corresponding to the SNMP message thus transmitted thereto back to the SNMP message transmission/reception unit 66. Then, the SNMP message transmission/reception unit 66 delivers the SNMP message of the response thus received, and the information of the transmission

25 source and transmission destination thereof to the proxy data assembly/disassembly unit 62. Then, the proxy data assembly/disassembly unit 62 delivers the information of the transmission destination and the

transmission source, and the PDU of the management  
protocol as the response to the address translation  
processing unit 63. Then, the address translation  
processing unit 63 subjects the transmission source  
5 address data and the transmission destination address  
data of the management protocol proxy data delivered  
thereto, and the address information within the PDU of  
the management protocol to the address translation to  
deliver the translation result to the proxy data  
10 disassembly/assembly unit 62. Then, the proxy data  
disassembly/assembly unit 62 assembles the information  
of the transmission destination and the transmission  
source, and the PDU of the management protocol in the  
form of the management protocol proxy data to deliver  
15 the data thus assembled to the interproxy communication  
unit 61. Then, the interproxy communication unit 61  
transmits the management protocol proxy data to the  
management protocol proxy 60a on the managing side, and  
also the management protocol proxy 60a on the managing  
20 side returns the PDU of the management protocol back to  
the manager 40.

Now, the ASN.1MIB define statement 64 is the  
MIB define statement described by the ASN.1 (Abstract  
Syntax Notation One) which is the standard description  
25 method for the MIB object described in RFC1212 (Concise  
MIB Definition) and the like. In general, the MIB  
define statement by ASN.1 is widely open to the public  
by a person who had defined the MIB module thereof. In

the present embodiment, since the address contained in Variable-Bindings of the protocol data unit of the management protocol is translated using the information which is obtained by analyzing the MIB define statement  
5 by ASN.1, the special define statement becomes unnecessary so that the configuration becomes simpler.

Fig. 13 is a block diagram showing a configuration of the management protocol proxy on the managing side.

10           The management protocol proxy 60a on the managing side includes: an SNMP message transmission/reception unit 66 for transmitting/receiving the SNMP message to/from an SNMP manager 41 on the manager 40; a proxy data assembly/disassembly unit 62 for processing  
15 the disassembly/assembly of the management protocol proxy data; and an interproxy communication unit 61 for processing the establishment of the interproxy communication path 70 distributed between the management protocol proxy 60b on the managed side and the unit 61,  
20 and the transmission/reception of the management protocol proxy data.

At the time when the SNMP message issued from the SNMP manager 41 on the manager 40 has been delivered to the management protocol proxy 60a on the  
25 managing side, the SNMP message transmission/reception unit 60 receives the SNMP message to deliver the SNMP message thus received to the proxy data assembly/disassembly unit 62. Then, the proxy data assembly/

disassembly unit 62 assembles the management protocol proxy data from the SNMP message thus delivered thereto, and the information of the transmission destination and the transmission source thereof to

5 deliver the management protocol proxy data thus assembled to the interproxy communication unit 61.

Then, the interproxy communication unit 61 transmits the management protocol proxy data thus delivered thereto to the management protocol proxy 60b on the

10 managed side. Further, the interproxy communication unit 61 receives the management protocol proxy data of the response returned from the management protocol proxy 60b on the managed side to deliver the management protocol proxy data thus received to the proxy data

15 assembly/disassembly unit 62. Then, the proxy data assembly/disassembly unit 62 fetches the information of the transmission source and the transmission destination, and the SNMP message from the management protocol proxy data to deliver the information and the message

20 thus fetched to the SNMP message transmission/reception unit 66. Then, the SNMP message transmission/reception unit 66 returns the SNMP message back to the SNMP message 41 on the manager 40 in accordance with the delivered information.

25 Fig. 14 shows one example of the management protocol proxy data which is transmitted/received on the interproxy communication path 70 distributed between the management protocol proxy 60a on the

manager side and the management protocol proxy 60b on the managed side, and also shows an example in the case where the management protocol is the SNMP. In this case, the management protocol proxy data is the data  
5 containing therein the information of the transmission source of the SNMP message, the information of the transmission destination of the SNMP message, and the SNMP PDU.

Fig. 2 is a diagram showing the packet of the  
10 normal SNMP message. By the way, the packet is shown only with respect to the upper part with respect to the IP layer as the network layer. In the normal SNMP packet, the information of the transmission source and the information of the transmission destination at the  
15 IP layer level become the transmission source and the transmission destination of the SNMP message itself as they are.

Fig. 3 is a diagram showing the packet of the management protocol proxy data in the case where the  
20 management protocol is the SNMP. By the way, the packet is shown only with respect to the upper part with respect to the IP layer as the network layer. In the packet of the management protocol proxy data, the transmission source or the transmission destination at  
25 the IP layer level is one of the management protocol proxies which are present in the both sides of the interproxy communication path 70, respectively, and the data of the transmission source and the transmission

destination of the SNMP message is contained in the form of the management protocol proxy data corresponding to the application layer in the packet. Therefore, the virtual address which is used for the address translation is not used as the transmission destination or the transmission source address of the actual communication packet. For this reason, even if the virtual address is used which is not allocated from the organ such as the NIC to the organization thereof, this does not impede the communication at the IP layer, i.e., at the network layer level at all.

In such a manner as described above, the addresses of the SNMP message transmission source and transmission destination on the management protocol proxy data are subjected to the address translation, whereby the virtual address which is not the proper global address can be used in the management address, and hence the private network can be subjected to the network management including the apparatuses each not having the global address.

Next, the proxy data assembly/disassembly unit 62 will hereinbelow be described with reference to Fig. 15, Fig. 17 and Fig. 18.

Fig. 15 is a block diagram showing a configuration of the proxy data assembly/disassembly unit 62.

The proxy data assembly/disassembly unit 62 includes: an assembly/disassembly processing unit 68

for executing the assembly/disassembly processing; and  
the other party proxy definition 69 in which the  
correspondence relationship between the transmission  
destination of the SNMP message and the other party to  
5 which the SNMP message is to be transmitted is defined.

Fig. 16 shows a definition example of the  
other party proxy definition.

A definition line 311 is a definition line  
exhibiting that the SNMP message in which a first octet  
10 of the transmission destination address is 100 is  
transmitted to the management protocol proxy in which  
the address is 200.10.20.30.

A definition line 312 is a definition line  
exhibiting that the SNMP message in which a first octet  
15 of the transmission destination address is 101 and a  
second octet thereof is 10 is transmitted to the  
management protocol proxy in which the address is  
200.10.20.30.

A definition line 313 is a definition line  
20 exhibiting that the SNMP message in which a first octet  
of the transmission destination address is 10, a second  
octet thereof is 20, and a third octet thereof is 80 is  
transmitted to the management protocol proxy in which  
the address is 230.51.62.72.

25 A definition line 314 is a definition line  
exhibiting that the SNMP message in which the trans-  
mission destination address is 120.60.11.8 is  
transmitted to the management protocol proxy in which



the address is 230.51.62.72.

By the way, the transmission address at this time is represented using the management address.

Fig. 17 shows a flow chart useful in explaining the proxy data assembly processing.

In Step 151, the SNMP message is received from the SNMP message transmission/reception unit.

In Step 152, both of the transmission source address and the transmission destination address are  
10 fetched from the IP header part of the SNMP message.

In Step 153, the SNMP PDU is fetched from the SNMP message.

In Step 154, the transmission source address, the transmission destination address and the SNMP PDU  
15 which have been fetched from the IP header part of the SNMP message are stored in the management protocol proxy data. In Step 155, the other party proxy address which is made correspond to the transmission destination address fetched from the IP header part of the  
20 SNMP message is retrieved in the other party proxy definition, and the other party proxy address of interest is decided as the transmission destination of the protocol proxy data.

In a manner as described above, the proxy  
25 data assembly/disassembly unit assembles the management protocol proxy data.

Fig. 18 shows a flow chart useful in explaining the proxy data disassembly processing.

In Step 161, the management protocol proxy data, and the address of the management protocol proxy as the other party which has transmitted the management protocol proxy data of interest are received from the interproxy communication part. In Step 162, the transmission source address, the transmission destination address and the SNMP PDU are fetched from the management protocol proxy data. In Step 163, the transmission source address and the transmission destination address which have been fetched from the management protocol proxy data are stored in the IP header part of the SNMP message. In Step 164, the SNMP PDU which has been fetched is stored in the SNMP message.

In a manner as described above, the proxy data assembly/disassembly unit disassembles the management protocol proxy data.

Fig. 19 is a block diagram showing a configuration of the address translation processing unit 63.

The address translation processing unit 63 includes: an SNMP message transmission source/transmission destination address translation unit 85 for translating the address of the transmission source and the address of the transmission destination of the SNMP message; and a PDU address translation unit 80 for translating the address information contained in the SNMP PDU. In addition, the PDU address translation

unit 80 includes: a PDU analysis/translation unit 81 for processing the analysis of the PDU and the address translation; an object identifier address translation unit 82 for processing the translation of the address which is contained as the object identifier of the address information contained in the PDU; an MIB instance value address translation unit 83 for processing the translation of the address which is contained as the MIB instance value of the address information contained in the PDU; and an agent-addr translation unit 84 for processing the translation of the address which is contained as the source address of trap (agent-addr) address of the address information contained in the PDU.

At the time when the management protocol proxy data has been delivered from the proxy data assembly/disassembly unit 62 to the address translation processing unit 63, first of all, the SNMP message transmission source/transmission destination address translation unit 85 carries out the address translation with respect to the transmission source and transmission destination of the SNMP message in the management protocol proxy data in accordance with the address translation definition 65. Next, the SNMP message transmission source/transmission destination address translation unit 85 delivers the management protocol proxy data to the PDU analysis/translation unit 81. Then, the PDU analysis/translation unit 81 carries out

the analysis with respect to the PDU in the delivered management protocol proxy data to extract the part, for which the address translation is required, from the PDU. First of all, the trap transmission source

5 address part is extracted from the PDU to be delivered to the trap transmission source address translation unit 84 which subjects in turn the trap transmission source address to the address translation in accordance with the address translation definition 65 to return

10 the resultant address information back to the PDU analysis/translation unit 81. Then, the PDU analysis/translation unit 81 replaces the trap transmission source address part of the PDU with the address, after completion of the address translation, which has been

15 received from the trap transmission source address translation unit 84. In addition, the MIB instance value in which the kind of data represents the IP address is extracted from the PDU to be delivered to the MIB instance value address translation unit 83.

20 Then, the MIB instance value address translation unit 83 subjects the MIB instance value to the address translation in accordance with the address translation definition 65 to return the resultant address information of the MIB instance value back to the PDU

25 analysis/translation unit 81. Then, the PDU analysis/translation unit 81 replaces the MIB instance value part of the PDU with the address, after completion of the address translation, which has been received from

the MIB instance value address translation unit 83. In addition, the object identifier of the MIB is extracted from the PDU to be delivered to the object identifier address translation unit 82. Then, the object

5 identifier address translation unit 82 subjects the IP address contained in the object identifier to the address translation in accordance with the ASN.1MIB define statement and the address translation definition 65 to return the resultant address information of the 10 object identifier back to the PDU analysis/translation unit 81. Then, the PDU analysis/translation unit 81 replaces the object identifier part of the MIB of the PDU with the address, after completion of the address translation, which has been received from the object 15 identifier address translation unit 82. Finally, the PDU analysis/translation unit returns the management protocol proxy data containing therein the PDU after completion of the address translation back to the proxy data assembly/disassembly unit 62.

20 In a manner as described above, the address translation processing unit can carry out the address translation with respect to the data of the management protocol.

Fig. 20 is a block diagram showing a configuration of the object identifier address translation 25 unit 82.

The object identifier address translation unit 82 includes: an ASN.1MIB define statement decoding

unit 88 for decoding the ASN.1MIB define statement 65;  
a translation subject object identifier extraction unit  
89 for extracting the object in which the object  
identifier needs to be translated on the basis of the  
5 definition contents of the decoded MIB; an object  
identifier comparison unit 86 for comparing the object  
identifier delivered from the PDU analysis/translation  
unit 81 with the object identifier extracted by the  
translation subject object identifier extraction unit  
10 89 to judge whether or not the delivered object  
identifier needs to be translated; and an address  
translation extraction unit 87 for on the basis of the  
definition information extracted by the translation  
subject object identifier extraction unit 89 and the  
15 address translation definition 65, subjecting the  
object identifier to the address translation.

First of all, the ASN.1MIB define statement  
decoding unit 88 reads out the ASN.1MIB define state-  
ment 65 to decode the ASN.1MIB define statement 65 thus  
20 read out to deliver the information of the MIB defini-  
tion obtained by the decoding to the translation  
subject object identifier extraction unit 89. Then,  
the translation subject object identifier extraction  
unit 89 extracts the MIB object having the possibility  
25 of containing the IP address in the object identifier  
from the delivered MIB statement to deliver the list of  
the object identifiers of the corresponding MIB object  
and the INDEX information as the definition information

of the corresponding MIB object to the object identifier comparison unit 86 and the address translation extraction unit 87, respectively. Now, by the MIB object having the possibility of containing the IP address in the object identifier is meant the MIB object representing the MIB table, i.e., the MIB object in which one or more MIB objects within the MIB table used as INDEX of the table are the IP addresses. Such an object is such that while when acquiring the instance as the value of the MIB object on the basis of the GET request or the like, INDEX as the instance identifier is added on the heels of the object identifier of the MIB object to be specified as the object identifier, since the IP address is used in INDEX at this time, there is a possibility that the IP address is contained in the object identifier. In addition, as for the INDEX information which is to be delivered to the address translation execution unit 87, in order that when a plurality of MIB objects are made correspond to one another as INDEXs of the MIB table, a part of the IP address of them may be translated, the information is delivered in which SYNTAXs as the kinds of MIB objects used as INDEXs are arranged in order. For example, in the case of the MIB table in which one MIB object of an integral number and the IP address are taken as INDEX, the instance identifier becomes the identifier having one sub-identifier for an integral number and four sub-identifiers for the IP address,

i.e., five sub-identifiers in total. In the address translation, since the second to fifth sub-identifiers of them need to be interpreted as the IP address to be translated, for INDEX, it is necessary to deliver the information having a set of one integral number and one IP address to the address translation execution unit 87.

Now, at the time when the object identifier in the PDU has been delivered from the PDU analysis/translation unit 81 to the object identifier address translation unit 82, first of all, the object identifier comparison unit 86 receives the object identifier. Then, the object identifier comparison unit 86 compares the object identifier delivered from the PDU analysis/translation unit 81 with the object identifier list of the translation subject extracted by the translation subject object identifier extraction unit 89. If the object identifier delivered from the PDU analysis/translation unit 81 is contained in the object identifier list of the translation subject, then the object identifier is delivered from the PDU analysis/translation unit 81 to the address translation execution unit 87. On the other hand, if the object identifier delivered from the PDU analysis/translation unit 81 is not contained in the object identifier list of the translation subject, then the object identifier delivered from the PDU analysis/translation unit 81 is not translated at all to be returned back to the PDU



analysis/translation unit 81 as it is.

Next, with respect to the object identifier delivered therefrom, first of all, the address translation execution unit 87 specifies the location of the IP address appearing in the object identifier, i.e., the translation location on the basis of the INDEX information delivered from the translation subject object extraction unit 89 and next, carries out the address translation on the basis of the address translation definition 65 to return the object identifier after completion of the address translation back to the PDU analysis/translation unit 81.

In a manner as described above, the object identifier address translation unit can subject the IP address contained in the object identifier of the MIB to the address translation.

The processing in the PDU analysis/translation unit will hereinbelow be described with reference to a flow chart shown in Fig. 21.

In Step 111, the data representing the kind of PDU is extracted from the PDU. In Step 112, the address translation direction is determined from the kind of PDU. By the address translation direction is meant whether the address in the PDU is translated from the management address into the real address or from the real address into the management address. For the PDU which is transmitted from the managing side to the managed side, the management address is translated into

the real address. For the PDU transmitted from the managed side to the managing side, the real address is translated into the management address. Whether the PDU is transmitted from the managing side to the managed side or from the managed side to the managing side is determined every kind of PDU, and hence the address translation direction can be determined from the kind of PDU in accordance with a table shown in Fig. 22. In Step 113, it is judged whether or not the kind of PDU is the SNMP trap. If it is judged in Step 113 that the kind of PDU is the SNMP trap, then the processing proceeds to Step 114. On the other hand, if it is judged in Step 113 that the kind of PDU is not the SNMP trap, then the processing proceeds to Step 117. In Step 114, the trap transmission source address is extracted from the PDU. In Step 115, the trap transmission source address extracted in Step 114 and the information of the address translation direction determined in Step 112 are delivered to the trap transmission source address translation unit and then the trap transmission source address after completion of the translation is received. In Step 116, the trap transmission source address of the PDU is replaced with the trap transmission source address, after completion of the translation, which has been received in Step 115. In Step 117, it is judged whether or not variableBindingList is present in the PDU. If it is judged in Step 117 that variableBindingList is present

in the PDU, then the processing proceeds to Step 118.

On the other hand, if it is judged in Step 117 that variableBindingList is absent in the PDU, then the processing in the PDU analysis/translation unit is

5 completed. In Step 118, one unprocessed variableBind is executed from variableBindingList. In Step 119, the object identifier and the value are extracted from variableBind extracted in Step 118. In Step 120, both of the MIB instance value extracted in Step 119 and the  
10 information of the translation direction determined in Step 112 are delivered to the MIB instance value address translation unit and then the MIB instance value after completion of the translation is received.

In Step 121, both of the object identifier extracted in

15 Step 119 and the information of the translation direction determined in Step 112 are delivered to the object identifier address translation unit and then the object identifier after completion of the translation is received. In Step 122, the object identifier of

20 variableBind of the PDU is replaced with the object identifier, after completion of the translation, which has been received in Step 121, and also the MIB instance value of variableBind is replaced with the MIB instance value, after completion of the translation,

25 which has been received in Step 120. In Step 123, it is judged whether or not the unprocessed variable-Binding still remains. If it is judged in Step 123 that the unprocessed variableBinding still remains,

then the processing proceeds to Step 118. On the other hand, if it is judged that the unprocessed variable-Binding does not yet remain, then the processing in the PDU analysis/translation unit is completed.

5           In a manner as described above, the address information in the PDU can be translated. Next, the processing in the translation subject object identifier extraction unit will hereinbelow be described with reference to a flow chart shown in Fig. 23.

10           In Step 131, one object identifier which is defined in the MIB statement is fetched. In Step 132, it is judged whether or not the object identifier fetched in Step 131 is the identifier representing the MIB table. If it is judged in Step 132 that the object  
15 identifier fetched in Step 131 is the identifier representing the MIB table, then the processing proceeds to Step 133. On the other hand, if it is judged in Step 132 that the object identifier fetched in Step 131 is not the identifier representing the MIB  
20 table, then the processing proceeds to Step 136. In Step 133, SYNTAX of the MIB object in the table which is specified as INDEX of the object identifier is extracted. In Step 134, it is judged whether or not there is even one object in which SYNTAX of the MIB  
25 object in the table extracted in Step 133 is SYNTAX representing the IP address. If it is judged in Step 134 that there is even one object in which SYNTAX is SYNTAX representing the IP address, then the processing

proceeds to Step 135. On the other hand, if it is judged in Step 134 that there is not even one object in which SYNTAX is SYNTAX representing the IP address, then the processing proceeds to Step 136. In Step 135, it is judged that the object identifier fetched in Step 131 is the object identifier of a subject of the translation.

On the other hand, in Step 136, it is judged that the object identifier fetched in Step 131 is not the object identifier of a subject of the translation. In Step 137, it is judged whether or not any of the unprocessed object identifiers still remains in the MIB define statement. If it is judged in Step 137 that any of the unprocessed object identifiers still remains in the MIB define statement, then the processing proceeds to Step 131. On the other hand, if it is judged in Step 137 that any of the unprocessed object identifiers does not yet remains in the MIB define statement, then the processing proceeds to Step 138. In Step 138, the object identifier comparison unit is informed of all of the object identifiers each of which has been judged to be a subject of the translation. In Step 139, the address translation execution unit is informed of all of the INDEX information of the object identifiers each of which has been judged to be a subject of the translation.

In a manner as described above, it is possible to realize the processing in the translation

subject object identifier extraction unit.

Fig. 24 shows a definition example of the address translation definition 65.

A definition line 301 is a definition example  
5 in the case where only a first octet of the IP address is translated. In this case, with respect to all of the real addresses in each of which the first octet is 10, the real address in which the first octet is translated into 100 becomes the management address.  
10 For example, in the case where the address 100.1.2.3 is present in the data of the management protocol which has been transmitted from the manager 40, the address of interest is translated into an address 10.1.2.3 through the address translation to be relayed to the  
15 managed node 50. On the contrary, in the case where the address 10.1.2.3 is present in the response from the managed node 50, the address of interest is translated into an address 100.1.2.3 through the address translation to be relayed to the manager 40. A  
20 definition line 302 is a definition example in the case where a first octet and a second octet of the IP address are both translated. In this case, with respect to all of the real addresses in each of which the first octet is 172 and the second octet is 16, the  
25 real address in which the first octet is translated into 101 and the second octet is translated into 10 becomes the management address. For example, in the case where the address 101.10.1.2 is present in the

data of the management protocol which has been transmitted from the manager 40, the address of interest is translated into an address 172.16.1.2 through the address translation to be relayed to the managed node 50. On the contrary, in the case where the address 172.16.1.2 is present in the response from the managed node 50, the address of interest is translated into an address 101.10.1.2 through the address translation to be relayed to the manager 40. A definition line 303 is a definition example in the case where a first octet, a second octet and a third octet of the IP address are all translated. In this case, with respect to all of the real addresses in each of which the first octet is 172, the second octet is 17 and the third octet is 50, the real address in which the first octet is translated into 110, the second octet is translated into 20 and the third octet is translated into 80 becomes the management address. For example, in the case where the address 110.20.80.1 is present in the data of the management protocol which has been transmitted from the manager 40, the address of interest is translated into an address 172.17.50.1 through the address translation to be relayed to the managed node 50. On the contrary, in the case where the address 172.17.50.1 is present in the response from the managed node 50, the address of interest is translated into an address 110.20.80.1 through the address translation to be relayed to the manager 40.

In addition, a definition line 304 is a definition example in the case where when all of the octets from the first octet to the fourth octet are translated. In this case, the real address in which the address is 5 192.168.20.5 is translated into the address 120.60.11.8 for management. For example, in the case where the address 120.60.11.8 is present in the data of the management protocol which has been transmitted from the manager 40, the address of interest is translated into 10 an address 192.168.20.5 through the address translation to be relayed to the managed node 50. On the contrary, in the case where the address 192.168.20.5 is present in the response from the managed node 50, the address of interest is translated into an address 120.60.11.8 15 through the address translation to be relayed to the manager 40.

Fig. 25 is a diagram showing an example of a configuration of another virtual network management system.

20 In this case, while the manager 40 and the management protocol proxy 60a on the manager side are present on the global network 10, it is possible to carry out the virtual network management using the management address without being different from the 25 case having the configuration shown in Fig. 1.

Fig. 26 and Fig. 27 are respectively block diagrams showing configurations of the management protocol proxies in still another embodiment and yet



another embodiment, i.e., embodiments in the case where the address translation is carried out by the management protocol proxy on the managing side.

In these cases as well, the address translation can be carried out in the same manner as that in the case where the address translation is carried out by the management protocol proxy on the managed side shown in Fig. 12 and Fig. 13. But, when the address translation is carried out in the management protocol proxy on the managing side, the address translation definition which is to be carried out in the management protocol proxy on the managing side is defined individually every private network on the managed side. For example, the address translation definition 65b and the address translation definition 65c are respectively defined for the private network B on the managed side and for the private network C on the managed side. As a result, even in the case where the private addresses of the managers conflict with each other in a plurality of private networks on the managed side as in the configuration shown in Fig. 9, the address translation can be made carried out properly.

Fig. 28 is a block diagram showing a configuration of the virtual network management system in a further embodiment, and Fig. 29 is a block diagram showing a configuration of the management protocol proxy on the managed side in the further embodiment. In these figures, each of the configurations is such

that the management protocol proxy on the managed side is operated on the same apparatus as the NAT conforming to RFC1631.

The configuration of this example is such  
5 that the manager 40 and the management protocol proxy 60a on the managing side are present on the global network 10, and the management address translation is carried out in the management protocol proxy on the managed side, and the management protocol proxy on the  
10 managed side is operated on the same apparatus as that of the NAT 20 conforming to RFC 1631.

Fig. 29 shows the configuration of the management protocol proxy 60b on the managed side which is operated on the same apparatus as that of the NAT 20  
15 not having the address translation function of the management protocol conforming to RFC1631. A point of difference from the configuration shown in Fig. 12 is that when the interproxy communication unit 61 is intended to communicate with the management protocol  
20 proxy 60a on the managing side, the communication is carried out through a global network side communication protocol processing unit 21, and when the SNMP message transmission/reception unit 66 transmits/receives the data to/from the managed node 50, the communication is  
25 carried out through a private network side communication protocol processing unit 23 of the NAT 20. By the way, as for the motion conforming to RFC1631 of the NAT 20, with respect to the packet which is intended to

pass through the associated apparatuses of the NAT 20 from the global network side to the private network side, first of all, the global network side communication protocol processing unit 21 catches the packet  
5 which is intended to pass therethrough to deliver the packet thus caught to an RFC1631 conformity address translation processing unit 22, and then the RFC1631 conformity address translation processing unit 22 carries out the address translation. Thereafter, the  
10 packet of interest is delivered to the private network side communication protocol processing unit 23 to be sent to the private network side by the private network side communication protocol processing unit 23.

On the contrary, with respect to the packet  
15 which is intended to pass through the associated apparatuses of the NAT 20 from the private network side to the global network side, first of all, the private network side communication protocol processing unit 23 catches the packet which is intended to pass there-  
20 through to deliver the packet thus caught to the RFC1631 conformity address translation processing unit 22 and then the RFC1631 conformity address translation processing unit 22 carries out the address translation. Thereafter, the packet is delivered to the global  
25 network side communication protocol processing unit 21 to be sent to the global network side by the the global network side communication protocol processing unit 21.

However, the communication made by the

interproxy communication unit 61 is the communication in which the address on the global network side of the apparatus in which the NAT and the management protocol proxy on the managed side are both operated is made  
5 either the transmission destination or the transmission source, but is not the communication in which the associated information is not intended to pass through the NAT 20. For this reason, the data is delivered from the global network side communication processing  
10 unit 21 to the interproxy communication unit 61 as it is without passing through the RFC1631 conformity address translation processing unit 22.

In addition, with respect to the communication as well made by the SNMP message transmission/  
15 reception unit 66, it is the communication in which the address on the private network side of the apparatus in which the NAT and the management protocol proxy on the managed side are both operated is made either the transmission destination or the transmission source,  
20 but is not the communication in which the associated information is not intended to pass through the NAT 20. For this reason, the data is delivered from the private network side communication processing unit 23 to the SNMP message transmission/reception unit 66 as it is  
25 without passing through the RFC1631 conformity address translation processing unit 22.

From the foregoing, it is possible that the management protocol proxy having the same configuration

as that of the management protocol proxy on the managed side shown in Fig. 12 is employed to be operated on the same apparatus as the NAT 20 to realize the virtual network management.

5           By the way, as has already been described, the processing in the management protocol proxy, as shown in the flow chart, can be realized in the form of the program.

10           Above, while the NAT has been described as the apparatus for carrying out the address translation of the IP layer (the NAT does not have the function of translating the address of the PDU part of the management protocol), in the case where the NAT has the function of carrying out the address translation of the  
15 IP layer and the function of translating the address of the PDU part of the management protocol, the NAT and the management protocol proxy server can be selectively utilized to carry out the address translation of the PDU part of the management protocol.

20           As set forth hereinabove, according to the present invention, the data communication can be carried out between the proxies of the management protocol, and also the data communication by the management protocol can be carried out between the  
25 nodes each not having the global address.

          Although the present invention has been described with reference to specific embodiments, these descriptions are not meant to be construed in a

limiting sense. Various modifications of the disclosed  
embodiments, as well as alternative embodiments of the  
invention will become apparent to persons skilled in  
the art upon reference to the description of the inven-  
5 tion. It should be appreciated by those skilled in the  
art that the conception and the specific embodiment  
disclosed may be readily utilized as a basis for  
modifying or designing other configurations for carry-  
ing out the same purpose of the present invention. It  
10 should also be realized by those skilled in the art  
that such equivalent configurations do not depart from  
the spirit and scope of the invention as set forth in  
the appended claims.

It is therefore contemplated that the claims  
15 will cover any such modifications or embodiments that  
fall within the true scope of the invention.